

MATERIAL SAFETY DATA SHEET

I. PRODUCT IDENTIFICATION

Name: Henry 331 "Super Patch" Latex Floor Patching Compound
Description: Plaster of Paris

II. TRANSPORTATION DATA

SHIPPING NAME: Not classified. HAZARD CLASS: N/A. ID#: N/A.
EMERGENCY ONLY CONTACT: CHEM-TEL-1-800-255-3924

III. HMIS (0=minimal hazard; 4 = severe hazard)

Health = 1 Flammability = 0 Reactivity = 0

IV. PRODUCT CONTENT

This product does not contain chemicals subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR 372. All components are on TSCA inventory. This product does NOT contain asbestos.

V. HAZARDOUS INGREDIENTS

INGREDIENT:	PERCENT	OCCUP. EXPOS. LMT.
Calcium Sulfate, CAS#7778-18-9 (Plaster of Paris)	55 - 60	TLV: 10 mg/m3 PEL: 15 mg/m3 respirable dust: 5 mg/m3
Limestone, CAS#1317-65-3	35 - 40	15 mg/m3 respirable dust: 5 mg/m3

VI. PHYSICAL DATA

APPEARANCE: White powder. ODOR: N/A. BOILING POINT: N/A. MELTING POINT: N/A. VAPOR PRESSURE: N/A. VAPOR DENSITY: N/A. % VOLATILE BY WEIGHT (30 min. @ 275°F): N/K. EVAPORATION RATE: N/A. SOLUBILITY IN WATER: < 1%. SPECIFIC GRAVITY: 2.85 - 2.95 WT/GAL: N/A

VII. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD): None. FLAMMABLE RANGE: LEL: N/A; UEL: N/A. EXTINGUISHING MEDIA: N/A. SPECIAL FIRE FIGHTING PROCEDURES: Protect fire fighters from toxic products of combustion by wearing self-contained breathing apparatus. UNUSUAL FIRE AND EXPLOSION HAZARDS: None

VIII. HEALTH HAZARD DATA

PRIMARY ROUTE(S) OF ENTRY: Inhalation and direct dermal exposure. TARGET ORGANS: Upper respiratory system, skin and eyes. EFFECTS OF OVEREXPOSURE: SKIN AND EYES: Prolonged or repeated overexposure to dust may cause slight transient irritation to the eyes and skin. INHALATION: Prolonged or repeated overexposure to dust may cause nose and throat irritation. CARCINOGENICITY: NTP: No. IARC Monographs: No. OSHA Regulated: No. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Existing skin conditions. Preexisting upper respiratory and lung disease such as, but not limited to bronchitis, emphysema, and asthma. FIRST AID PROCEDURES: SKIN AND EYES: In case of eye contact, flush eyes with plenty of water continuously for fifteen (15) minutes; get medical attention immediately. Wash skin thoroughly with soap and water or hand cleaner. Seek medical attention if symptoms persist. Wash clothing before reusing. INHALATION: Remove to fresh air.

IX. REACTIVITY DATA

STABILITY: Stable. INCOMPATIBILITY: N/K. HAZARDOUS DECOMPOSITION PRODUCTS: N/K. HAZARDOUS POLYMERIZATION: Will not occur.

HENRY®

331

Prepared 5/00 - Replaces 3/98

The W.W. Henry Company
400 Ardex Park Drive
Aliquippa, PA 15001
(724) 203-8499

Visit our Website: <http://www.wwhenry.com>

X. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Pick up material and place into DOT approved container. Avoid creating dust. WASTE DISPOSAL METHOD: Dispose of container and any unused contents in accordance with Federal, State, and Local Waste Disposal Regulations. Do not flush unused contents or residue down drains. Do not reuse container.

XI. SAFE HANDLING AND USE INFORMATION

VENTILATION: Normal, ambient ventilation should be sufficient. Avoid creating dust. RESPIRATORY PROTECTION: Should not be required. If work process generates excessive quantities of dust, or exposures in excess of the PEL, wear respirator approved for pneumoconiosis-producing dusts. SKIN AND EYE PROTECTION: It is always a good safety practice to avoid contact with eyes and prolonged contact with skin. Use spectacle-type glasses to avoid getting in eyes, and latex or rubber gloves to prevent skin contact.

XII. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a dry place. Avoid breakage of bagged material. OTHER PRECAUTIONS: Do not use for any medical application. Failure to follow this instruction may cause severe burns. WORK SITE ENVIRONMENT: Initially there may be a potential adverse impact on indoor air quality within the general work area during the installation process. Therefore you should advise the building manager or other appropriate person that: • It will be necessary to establish and maintain adequate ventilation of the work area, without causing the entry of contaminants to other parts of building; and • Persons who are sensitive to odors and/or chemicals should be advised to avoid the work area during this process.

The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

N/A - not applicable or not available
N/K - none known or not known